

## **ISAL**

# PIXIE SMART AC CONTROLLER

#PC214AC/DK/BTAM

- ► DAIKIN™ Ducted Aircon
- Users must notify AC installer that the PIXIE Smart AC controller is being used and installed by them into the P1 & P2 terminals of the indoor unit.
- \*Standard\* on-wall AC controller from AC supplier must still be installed.



Applications

Ideal for smart control and integration of new and existing DAIKIN™ ducted aircon systems into your PIXIE Smart home.

Customer wanting remote access must also install PIXIE Gateway SGW3BTAM

SCAN ME



Download the PIXIE and PIXIE PLUS Apps







## #PC214AC/DK/BTAM PIXIE SMART AC CONTROLLER

The PIXIE PC214AC/DK/BTAM Smart AC Controller (PAC) is designed for integrating DAIKIN™ Ducted AC system into the PIXE Smart home ecosystem via Bluetooth Mesh. Simple installation and access to essential AC control capabilities such as on/off power control, mode select (cool, heat, dry, fan), temperature setpoint and fan speed for DAIKIN™ ducted systems.

### **Features**

- Control and integration of DAIKIN™ ducted AC systems.
- Works with PIXIE and PIXIE PLUS apps over Bluetooth Mesh
- No requirement for Wi-Fi or internet for in-home operation, control and integration. Simple Install. Scan Control process to setup.
- Single connection point to P1 & P2 terminals on DAIKIN™ indoor unit.
- Users wanting remote access control and voice operation, should use PIXIE PLUS and also install a PIXIE Gateway on site (SGW3BTAM).
- On-device Power and Mode select buttons + LED indicators enable simple installation testing and operational status feedback.
- Scheduling, Scenes and integration with other PIXIE devices and functions is setup in the PIXIE Apps and fully compatible with up to 8 PIXIE Touch Panels

## **Product Specifications**

Input	24V AC from indoor unit
Control provided	On/Off power control,
	mode select (cool, heat,
	dry, fan), temperature
	setpoint and fan speed
PIXIE Device Type	PIXIE Master Device





## **PIXIE SMART** AC CONTROLLER

#PC214AC/DK/BTAM

### Related products

**PIXIE Smart Zone** Controller #SZC248N/R/BTAM

**PIXIE Gateway G3** #SGW3BTAM

## **SCAN ME**



Download the PIXIE and PIXIE PLUS Apps





## **In App Operation**







Operating Zones\*

DAIKIN™ AC Control can be a part of Schedules, Scenes and PROGRAMode for sophisticated control and conditional operations in a fully integrated smart home solution. \*When combined with the PIXIE Smart Zone Controller, users are in full control of all AC control parameters and manage energy and comfort, room-to-room using PIXIE smart home ecosystem.

#### Compatible with DAIKIN™ Indoor Units - Ducted Units

#### **Premium Inverter Ducted**

FDYA 71/85/100/125/140/160 AV19, FDYQ 180/200/250 LCV1

#### **Inverter Ducted**

FDYAN 50/60/71/85/100/125/140/160 AV1, FDYQN 180/200 LCV1, FDYQN250LBV1

#### Slimline Ducted

FBA 50/60 BAVMA, FBA 71/85/100/125/140 BVMA

#### **Bulkhead System**

FDYBA 25/35/50/60/71 AV

## Important Information:

Ducted = 1-2 PIXIE AC Controllers (for indoor units) and PIXIE Smart Zone Controllers for Zone control. VRV (FX-series indoor units) = must have one PIXIE AC Controller per room.

DAIKIN™ indoor units can have a maximum of only 2 controllers attached. One controller will be the standard DAIKIN™ remote wall panel. The PAC is the 2<sup>nd</sup> device and no DAIKIN<sup>TM</sup> Airbase<sup>TM</sup> or other remote devices are required or able to be connected.















